




Seed Cleaning with a Winnowing Chamber

Chaplin, G.E.

Publication date:
1985

Document version
Publisher's PDF, also known as Version of record

Citation for published version (APA):
Chaplin, G. E. (1985). *Seed Cleaning with a Winnowing Chamber*. Danida Forest Seed Centre. Technical Note no. 25



TECHNICAL NOTE NO. 25
Juni 1985 (re-issued January 1995)

**SEED CLEANING WITH A
WINNOWER CHAMBER**

compiled by
G.E. Chaplin



Titel

Seed cleaning with a winnowing chamber

Authors

G.E. Chaplin

Publisher

Danida Forest Seed Centre

Series - title and no.

Technical Note no. 25

DTP

Melita Jørgensen

Citation

Chaplin, G.E. 1995. Seed cleaning with a winnowing chamber

Citation allowed with clear source indication

Written permission is required if you wish to use Forest & Landscape's name and/or any part of this report for sales and advertising purposes.

The report is available free of charge

SL-International@kvl.dk

Electronic Version

www.SL.life.ku.dk

ISSN 0902-3224

TECHNICAL NOTE NO. 25 - JUNE 1985

(Re-issued January 1995)

SEED CLEANING WITH A WINNOWER CHAMBER

by

G.E. Chaplin

Danida Forest Seed Centre • Krogerupvej 21
DK-3050 Humlebaek • Denmark

CONTENTS

1.	INTRODUCTION	1
2.	DESCRIPTION	1
3.	FUNCTION	1
4.	USE	2

1. INTRODUCTION

A locally made seed winnowing chamber is described. It works with a stream of air from an electric fan and can be used to separate debris and empty seeds from dry seed batches.

This note was originally sent out as Forest Research Note 1/84 from the Forestry Division Munda, Solomon Islands, July 1984.

2. DESCRIPTION

The winnowing chamber is made up of three separate sections:

1. Wind funnel; made of hardboard and beading with two sizes depending on seed bulk.
2. Centre section; made of hardboard base and sides with an elevated central section with a formica top which slopes down against wind direction.
3. Gauze cage; made of gauze mounted on beading.

All three sections fit together into a continuous chamber. The electric fan is placed at the far end of the wind funnel. The draught strength is varied by strength of fan and proximity to the winnowing slope.

3. FUNCTION

The chamber is used to clean dry seed that is mixed with light debris. The unsorted seed is dropped onto the sloping formica top. There are two variables:

- a. the height of the drop
- b. the position on slope.

Usually the unsorted seed of *Swietenia macrophylla* is dropped from about 30 cm onto the middle of the formica slope. The unsorted seed may be dropped by hand or from a container to ensure a more uniform flow.

Adjustment of the variables and of draught strength will determine the efficiency of separation and speed of work. Skill of operation is rapidly acquired but requires fine judgement and attention.

Seeds need to be winnowed repeatedly as rarely does one passage remove all the debris.

4. USE

This locally made winnowing chamber is now used routinely to separate the broken wings and empty seeds of *S. macrophylla*. All of the debris and virtually all the empty seeds can be separated by a skilled operator.


The dried pulp debris of *Campnosperma brevipetiolata* has been separated from the seed. The pod debris and detached funicles of *Acacia mangium* are also easily separated.

This winnowing chamber is a useful addition to a seed handling facility and can be used to separate debris and empty seed from the full seed of other species in addition to those already cleaned in this way at Munda.


SEED WINNOWING CHAMBER

ELEVATION


wind direction



WIND FUNNEL





GAUZE CAGE, TIMBER FRAMED




CENTRAL SECTION WITH WINNOWING SLOPE

PLAN




optional smaller frame for less bulky seeds



formica top, sloped



SEED WINNOWING CHAMBER



GAUZE CAGE, TIMBER FRAMED

CENTRAL SECTION WITH WINNOWING SLOPE

WIND FUNNEL

PLAN

